



685 WALL BASE ADHESIVE

DESCRIPTION

Healthy Home 685 Wall Base Adhesive is a solvent free, non-flammable, freeze-thaw stable, acrylic latex-based adhesive specifically designed for the installation of vinyl, TS rubber, thermoplastic rubber, or carpet wall base. This adhesive is designed for use over almost any porous, clean, dry, and structurally sound wall. Healthy Home Adhesives 685 Wall Base Adhesive can be applied directly to the wall base or directly to the wall.

Wall Surfaces

- › Wood
- › Plywood
- › Painted Walls
- › Gypsum Drywall
- › Plaster
- › Brick
- › Concrete

NOTE: Not recommended over non-porous walls including vinyl wall coverings. Installing over a non-porous substrate will not allow the adhesive to properly dry.

Coverage

30 oz Cartridge	(1) Gallon Pail	(4) Gallon Pail
50 Lin. Ft of 4" base with 1/8" bead	2.5" base - 300 Lin. Ft	2.5" base - 1200 Lin. Ft
	4" base - 250 Lin. Ft	4" base - 1000 Lin. Ft
	6" base - 160 Lin. Ft	6" base - 640 Lin. Ft

*Spread rate will vary based on substrate texture and absorption rate, trowel angle and other factors.

Shelf Life

Unopened packaging stored in proper conditions have a shelf life of 2 years.

INSTALLATION INSTRUCTIONS

All subfloor preparation instructions from the flooring manufacturer and current industry standards must be followed. Spread Adhesive either on the wall or the surface of the wall base using a 1/8" square notch trowel. Ensure a proper gap is left at the top of the wall base that will allow the adhesive to cover the very top of the base, but not "ooze" from the top of the base. Any adhesive that gets on the wall will need to be cleaned using a clean rag and water when wet or use Mineral Spirits when dried. Follow acclimation instructions for the wall base material. Most require 24-48 hours of acclimation before installation. This prevents the wall base from expanding or contracting after installation.

For Technical Support contact your local Healthy Home Adhesives Sales Manager or call 877-458-3833.

RESTRICTIONS

1. Refer to flooring manufacturer for recommendation.
2. For interior installations only.
3. It is the sole responsibility of the installer to determine the suitability and compatibility of the adhesive for the intended application.

CLEAN UP

Fresh adhesive can be cleaned up using water and a clean cloth, dried adhesive will require the use of mineral spirits or other clear solvent.





FIRST AID MEASURES

- › After inhalation: Supply fresh air or oxygen; call for doctor. In case of unconsciousness place patient stably in side position for transportation.
- › After skin contact: Immediately wash with water and soap and rinse thoroughly.
- › After eye contact: Rinse opened eye for several minutes under running water.
- › After swallowing: Do not induce vomiting; immediately call for medical help.

CALIFORNIA VOC COMPLIANCE

Solvent Free Product

SCAQMD Rule 1168: VOC Compliant

SCAQMD Rule 443.1: Grams per Liter of Material <1 gram/liter. Grams per Liter of Coating <1 gram/liter.

WARRANTY

Healthy Home Adhesives offers a limited liability warranty for this material when used in accordance with the label and TDS.