

# EF5000 CARPET PAD CEMENT EXTREMELY FLAMMABLE

## FOR PROFESSIONAL USE ONLY

**DESCRIPTION:** Healthy Home EF5000 Carpet Pad Adhesive is an Extremely Flammable solvent-based pad adhesive that is recommended for permanently fastening carpet padding over any approved flooring surface. EF5000 has strong initial tack and high strength, this prevents movement of padding during stretching or life of the carpet. NOTE: Due to continuing development of new and different types of backings, padding and methods of application, we recommend that any unfamiliar materials be thoroughly tested before attempting a complete installation.

### **DIRECTIONS:**

- 1. The floor must be clean, dry, and free of dust, dirt and grease or oil.
- 2. There is an inner seal under the screw cap on the container that should be pierced or removed. Punch a 1/8" diameter hole in this seal.
- 3. Pour adhesive on the floor in a 3" or 4" bead from the wall. Use a zigzag pattern at the padding seam.
- 4. Let the adhesive dry two to five minutes.
- 5. Drop padding into exact position desired and apply pressure by walking over the adhesive area.
- 6. Install carpet immediately after laying padding. Padding will not slip once placed into adhesive.
- 7. It is the sole responsibility of the installer to determine the suitability and compatibility of the adhesive for the end user's intended use.

**CLEAN-UP:** Mineral Spirits can be used to clean up excess adhesive or spills.

#### PRECAUTIONARY STATEMENTS

Keep containers tightly closed. Store in cool well ventilated place. Keep away from heat/sparks/open flame, No smoking. Only use non-spark tools. Use explosion proof electrical equipment. Take precautionary measures against static discharge. Avoid gross contamination of skin. Avoid contact with eyes by wearing safety glasses. If concentration levels exceed TWA use only NIOSH certified respiratory equipment. READ SAFETY DATA SHEETS BEFORE USING THIS PRODUCT.

#### HAZARD STATEMENT

#### HIGHLY FLAMMABLE LIQUIDS AND VAPORS

HIGHLY FLAMMABLE LIQUID AND VAPOR. MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAY. CAUSES SKIN IRRITATION. MAY CAUSE DROWSINESS OR DIZZINESS. SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD. MAY CAUSE DAMAGE TO ORGANS, NERVOUS SYSTEM THROUGH PROLONGED OR REPEATED EXPOSURE IF SWALLOWED.

DO NOT SMOKE. CLOSE CONTAINERS TIGHTLY AFTER EACH USE.

PROVIDE ADEQUATE VENTILATION DURING APPLICATION AND DRYING CYCLES.

KEEP OUT OF THE REACH OF CHILDREN

IN CASE OF FIRE: Use Water spray; Alcohol resistant foam; Dry Chemical, Carbon Dioxide.

FIRST AID: INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give Oxygen. SKIN: Immediately flush with large amounts of water for 15 minutes, use soap if available. Get medical attention. INGESTION: Do not induce vomiting! If swallowed, immediately contact a physician or Poison Control Center. EYES: Flush eyes with water for 15 minutes while holding eyelids apart; seek immediate medical attention.

EMERGENCY CONTACT & PHONE NO: Healthy Home Adhesives 715 N. Murray Ave. Anderson, SC 29625 · 1-877-458-3833

